




Yoke Grade 10 Eye Grab Hook EN1677-1+2

The William Hackett Grade 10 forged lifting components are manufactured by YOKE from alloy steel in accordance with EN1677. All forged components are individually magnaflux crack detected after heat treatment, they are then individually proof load tested to 2.5 times working load limit in accordance with EN1677. Only components fully compliant with all aspects of EN1677 can be used in chain slings certified to EN818-4. The William Hackett Grade 10 lifting components are suitable for use in a temperature range of -40°C up to 200°C without reduction in working load limit. Testing according to ASTM A952/A - DIN PAS 1061



METRIC SPECIFICATIONS

| Part Code | Chain Size mm | A mm | F mm | G mm | K mm | P mm | WLL tonnes | Box Quantity | Mass Kg |
|-----------|---------------|------|------|------|------|------|------------|--------------|---------|
| X-041-06 | 6 | 13 | 26 | 8 | 50 | 8 | 1.4 | 100 | 0.2 |
| X-041-07 | 7,8 | 16 | 30 | 9 | 62 | 10 | 2.5 | 80 | 0.3 |
| X-041-10 | 10 | 20 | 40 | 13 | 82 | 13 | 4.0 | 40 | 0.6 |
| X-041-13 | 13 | 26 | 52 | 16 | 107 | 17 | 6.7 | 12 | 1.4 |
| X-041-16 | 16 | 30 | 57 | 20 | 132 | 21 | 10.0 | 10 | 2.4 |
| X-041-20 | 20 | 38 | 73 | 24 | 147 | 23 | 16.0 | 6 | 4.0 |
| X-041-22 | 22 | 38 | 70 | 26 | 164 | 26 | 19.0 | 5 | 5.0 |
| X-041-26 | 26 | 50 | 100 | 32 | 207 | 33 | 26.5 | 2 | 10.1 |

IMPERIAL SPECIFICATIONS

| Part Code | Chain Size inch | A inch | F inch | G inch | K inch | P inch | WLL lbs | Box Quantity | Mass lbs |
|-----------|-----------------|--------|--------|--------|--------|--------|---------|--------------|----------|
| X-041-06 | 1/4 | 0.51 | 1.02 | 0.31 | 1.97 | 0.31 | 3000 | 100 | 0.44 |
| X-041-07 | 5/16 | 0.63 | 1.18 | 0.35 | 2.40 | 0.39 | 5500 | 80 | 0.66 |
| X-041-10 | 3/8 | 0.78 | 1.57 | 0.51 | 3.23 | 0.51 | 8800 | 40 | 1.32 |
| X-041-13 | 1/2 | 1.02 | 2.05 | 0.69 | 4.21 | 0.67 | 14700 | 12 | 3.08 |
| X-041-16 | 5/8 | 1.81 | 2.24 | 0.78 | 5.19 | 0.82 | 22000 | 10 | 5.29 |
| X-041-20 | 3/4 | 1.49 | 2.87 | 0.94 | 5.78 | 0.91 | 35200 | 6 | 8.81 |

| | | | | | | | | | |
|----------|-----|------|------|------|------|------|-------|---|-------|
| X-041-22 | 7/8 | 1.49 | 2.75 | 1.02 | 6.45 | 1.02 | 41800 | 5 | 11.02 |
| X-041-26 | 1 | 1.97 | 3.94 | 1.29 | 8.14 | 1.29 | 58400 | 2 | 22.26 |



William Hackett

William Hackett Lifting Products Ltd Oak Drive, Lionheart Enterprise Park, Alnwick, Northumberland NE66 2EU
 Email: liftingsales@williamhackett.co.uk Tel: +44 (0)1665 604200 Fax: +44 (0)1665 604204

William Hackett Chain Products Ltd Maypole Fields, Cradley, Halesowen, West Midlands B63 2QE.
 Email: info@williamhackett.co.uk Tel: +44 (0)1384 569431 Fax: +44 (0)1384 639157

Web: www.williamhackett.co.uk



Better connected with William Hackett