



Pressure gauges model GGY

The use of pressure gauges is recommended when the operating pressure (the force of the connected cylinder) should be monitored. Yale pressure gauges are equipped with a stainless steel housing and an acrylic plastic face cover plate.

To absorb pressure shocks gauges are glycerine-filled, thus contributing to a long service life. Also, when fitted to a motor pump, the pointer will stay jitterfree.

For the calculation of applied cylinder forces corresponding converting charts (pressure vs. force) can be supplied for all Yale hydraulic cylinders free of charge.

Technical data model GGY

Model	EAN-No. 4025092*	Pressure range bar	Scale diameter mm	Glycerine- damped	Oil port DIN 16288	Spanner size	Accuracy class %
GGY-631	*154796	0 - 1000	63	yes	G 1/4	14	1.6
GGY-632	*155120	0 - 1000	63	yes	1/4 NPT	14	1.6
GGY-633	*155274	0 - 160	63	yes	G 1/4	14	1.6
GGY-634	*155281	0 - 250	63	yes	G 1/4	14	1.6
GGY-635	*155298	0 - 400	63	yes	G 1/4	14	1.6
GGY-636	*155304	0 - 600	63	yes	G 1/4	14	1.6
GGY-1001	*154802	0 - 1000	100	yes	G 1/2	22	1.0
GGY-1001 SZ ¹	*155168	0 - 1000	100	yes	G 1/2	22	1.0
GGY-1004	*155151	0 - 700	100	yes	G 1/2	22	1.0
GGY-1005	*159203	0 - 160	100	yes	G 1/2	22	1.0
GGY-1002	*155137	0 - 250	100	yes	G 1/2	22	1.0
GGY-1003	*155144	0 - 400	100	yes	G 1/2	22	1.0
GGY-2500	*155113	0 - 2500	100	yes	G 1/2	22	1.6

¹ GGY-1001 SZ = with maximum pointer



Pressure gauge model GYA-63

Consisting of pressure gauge GGY-632 (diameter Ø 63 mm, glycerine-damped) and corresponding gauge adaptor. This pressure gauge set is suitable for connection to all HPS hand pumps.

Assembled ready to use, compact design with 45° inclination for easy reading.

Technical data model GYA-63

Model	EAN-No. 4025092*	Pressure gauge bar	Oil port pump	Oil port hose	Weight kg
GYA-63	*156103	0 - 1000 bar, Ø 63 mm, glycerine-damped	3/8-NPT outer	3/8-NPT inner	0.5