



Vantage

Rigger Safety Harness

Technical Data Sheet

The Vantage Rigger Harness is Guardian's premium Rope Access harness designed for suspended work tasks. The addition of waist belt and leg pads provide support when suspended or work positioning. The waist belt includes multiple attachments and tool loops. Variants come with attachment points for the connection of a Croll/chest ascender (available separately).

Key Features

- Dual lanyard keepers
- Composite breathable shoulder padding
- Water-repellent contrasting core webbing for easy inspection
- 5 connection points
- Tool loops
- Adjustable leg extensions

Standards

- EN 361
- EN 358
- EN 813

For more information please call:

+44 (0) 1795 580 333

or email:

enquiries@guardianfall.com

guardianfall.com





Vantage

Rigger Safety Harness

Technical Data Sheet



Prod. Code	Description	Sizes	User Weight Range
48100 / 48101 / 48102	5 D-rings, pass-through buckles, waist belt	XS-S / M-L / XL-XXL	59 kg - 150 kg
48103 / 48104 / 48105	5 D-rings, pass-through buckles, waist belt, Croll/chest ascender	XS-S / M-L / XL-XXL	59 kg - 150 kg
48106 / 48107 / 48108	5 D-rings, quick-connect buckles, waist belt	XS-S / M-L / XL-XXL	59 kg - 150 kg
48109 / 48110 / 48111	5 D-rings, quick-connect buckles, waist belt, Croll/chest ascender	XS-S / M-L / XL-XXL	59 kg - 150 kg






Materials

 Polyester, galvanised steel, carbon steel, powder coated aluminium

Harness Weight

- 1.2 kg - 1.7 kg

Sizing Chart



Lifespan

Guardian products that consist of textile components of any kind have a maximum lifespan of 10 years from the date of manufacture.

Cleaning

Textiles must only be cleaned with plain water (not exceeding 50°C) or, if plain water is not sufficient, with a mild soap/water solution.

Inspection

Prior to EACH use, inspect the equipment and connection points for signs of deficiencies, including, but not limited to, corrosion, deformation, pits, burrs, rough surfaces, sharp edges, cracking, rust, paint build-up, excessive heating, alteration, broken stitching, fraying, missing or illegible labels.

Compliance

This product is fully compliant with the following safety regulations: **EN361**, **EN358** and **EN1813**



